



NAS Gyrotory Sifters

Deck	Model	Sieve dimension width * Length mm	Positive displacement stroke mm	Power kW	Rounds per min r/min	A mm	B mm	C mm	D mm	Weight kg
1	NAFS0515	500X1500	52	1.5	940	2235	700	730	810	350
1	NAFS1021	1000X2100	64	2.2	960	3280	960	1156	1200	960
1	NAFS1030	1000X3000	64	4	960	4485	1050	1156	1200	1100
1	NAFS1530	1500X3000	64	5.5	960	4236	1360	1778	1892	2300
1	NAFS1836	1800X3600	76	7.5	960	5305	1500	2180	2430	3600
1	NAFS2050	2000x5000	92	11	960	6770	1980	2245	2230	5000
2	NAFS0515	500X1500	52	1.5	940	2235	700	730	810	400
2	NAFS1021	1000X2100	64	2.2	960	3280	960	1156	1200	1080
2	NAFS1030	1000X3000	64	4	960	4485	1050	1156	1200	1230
2	NAFS1530	1500X3000	64	5.5	960	4236	1360	1778	1892	2600
2	NAFS1836	1800X3600	76	7.5	960	5305	1500	2180	2430	3900
2	NAFS2050	2000x5000	92	11	960	6770	1980	2245	2230	5200
3	NAFS0515	500X1500	52	1.5	940	2235	760	730	810	450
3	NAFS1021	1000X2100	64	2.2	960	3280	1050	1156	1200	1250
3	NAFS1030	1000X3000	64	4	960	4485	1080	1156	1200	1500
3	NAFS1530	1500X3000	64	5.5	960	4236	1460	1778	1892	3200
3	NAFS1836	1800X3600	76	7.5	960	5305	1560	2180	2430	4100
3	NAFS2050	2000x5000	92	11	960	6770	2040	2245	2230	5500